

WISI DM 17 A

Passive headend combiner



Description

At a glance:

- Compact design, rack mounted
- High isolation
- Low insertion loss
- Full bandwidth from 5...1000 MHz
- Front panel test port for easy monitoring

Technical data

Frequency range	5...1000 MHz
Input impedance	75 Ω
Input return loss	>18 dB typ., min. 14 dB dB
Number of taps	12
Output impedance	75 Ω
Output return loss	>18 dB typ., min 13 dB dB
Tap loss IN-Out	1...12 < 18 dB (\pm 1,5 dB)
Amplitude response (O-E)	<1,5 dB
Isolation Out-Out	>40 dB typ., min. 36 dB dB
Isolation Out-Out	>38 dB typ., min. 32 dB dB
Test Port	-20 dB
RF-screening	>110 dB
Power passing	V DC none

General data

Dimensions (width x height x depth)	483x44x124 mm
-------------------------------------	---------------

Connectors

Input	1x F-connector
Output	12x F-connector
test	1x F-connector
Temperature range	-20...+55 °C

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	mm
Packaging volume sales unit	dm ³
Gross weight sales unit	1.360 kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm ³
Gross weight shipping unit	kg
EAN	4010056731960
Article number	73196
Customs tariff number	8529109500