With user-friendly enhancements, Motorola's SURFboard® SB4200 Cable Modem is made for the marketplace.

The latest addition to Motorola's SURFboard Cable Modem family, the SURFboard SB4200, has been redesigned with the consumer in mind. The Motorola SURFboard SB4200 features a user-friendly, convenient, top-mounted stand-by switch. The stand-by switch disconnects the USB and Ethernet connection to the CPE without disconnecting the cable modem from the RF network, providing security and flexibility. Competitively priced, the SB4200 includes all the features of previous SURFboard Cable Modems, including USB connectivity, software upgrades available over the network, advanced RF design, top-notch field reliability and high-

performance processors. It offers both Ethernet and USB interface connectivity to help ensure compatibility with almost any PC or Macintosh network-ready

computer system. And its 10/100BaseT auto sensing Ethernet lines allow for seamless communications. Plus, it's hardware-ready to support DOCSIS 1.1 specifications, ensuring advanced Quality of Service (QoS).





- DOCSIS 1.0 CableLabs Certified
- User-friendly, top-mounted stand-by switch enhances security and convenience
- LED on the front panel to indicate stand-by status
- USB network connectivity simplifies installation
- Capable of downloading at speeds up to 100 times faster than a 28.8k analog phone modem*
- No telephone lines needed—always on, always connected
- Compatible with Windows 95/98/2000/Me/NT/XP/Mac/UNIX
- Supports up to 32 users—ideal for home and small businesses
- Attractive vertical design saves desk space



FEATURES

- DOCSIS 1.0 compliant
- DOCSIS 1.1 hardware based
- USB for Windows 98/2000/Me/XP
- Supports up to 32 users (1 via USB and up to 31 via Ethernet or 32 users on Ethernet)
- Ethernet and USB connections are bridged allowing LAN traffic between USB device and Ethernet LAN
- 10/100BaseT Ethernet (auto sensing)
- Remote management via SNMP
- Software upgradeable over the network
- Internal power supply
- Top-mounted stand-by switch enhances network security to end-user
- Platform independent modem with HTML-based user interface for status troubleshooting
- Front panel LEDs for easy troubleshooting
- Multi-language user guide
- ➤ Global safety approval & certificates:
 - CB scheme (EN60950/IEC950)
 - CE-Evaluation test report (EN55022/EN55024)

SPECIFICATIONS

DOWNSTREAM

64 an 256 OAM

MODULATION
Maximum Data Rate*38 Mbps
Bandwidth6 MHz
Symbol Rate
Symbol Rate
Operating Level Range
Input Impedance
Frequency Range

Madulation

UPSTREAM

Modulation	. 16 QAM or QPSK
Maximum Data Rate	. 10 Mbps
Bandwidth	. 200 kHz, 400 kHz, 800 kHz,
	1.6 MHz, 3.2 MHz
Symbol Rates	. 160, 320, 640, 1280 and
	2560 ksym/s
Operating Level Range	. +8 to +55 dBmV (16QAM)
	+8 to +58 dBmV (QPSK)
Output Impedance	. 75 Ω (nominal)
Frequency Range	. 5 to 42 MHz (edge to edge)

GENERAL

Cable Interface	. F-Connector, female, 75 Ω
CPE Network Interface	. USB, Ethernet 10/100BaseT
	(auto sensing)
Data Protocol	. TCP/IP
Dimensions	. 7.2" H x 2.0" W x 7.8" L
Power	. 9 Watts (nominal)
Input Power	. 100-240 VAC, 50-60 Hz

ENVIRONMENTAL

Operating Temperature	0° to 40° C
Storage Temperature	30° to 80° C
Operating Humidity	0 to 95% R.H. non-condensing

CONCLUSION

Designed with the consumer in mind, the Motorola SB4200 Cable Modem is ready for high-speed surfing. It's competitively priced and equipped with a top-mounted stand-by switch for enhanced end user security. The SB4200 simplifies installation with its USB interface and is also hardware-ready to support DOCSIS 1.1 specifications, ensuring advanced Quality of Service (QoS), excellent performance, seamless functionality, exceptional value... that's innovative technology.

^{*} When compared to traditional 28.8k analog modems. Actual speeds will vary, and are often less than the maximum possible. Upload and download speeds are affected by several factors including, but not limited to: network traffic and services offered by your cable operator or broadband service provider, computer equipment, type of server, number of connections to server, and availability of Internet router(s).



MOTOROLA, the Stylized M Logo and all other trademarks indicated as such herein are trademarks of Motorola, Inc. ® Reg. U.S. Pat. & Tm. Off. All other product or service names are the property of their respective owners.

^{© 2002} Motorola, Inc. All rights reserved. Printed in the U.S.A.