

General introduction

Specification:

- DVB-S/S2
- Demodulation QPSK, 8PSK, 16APSK, 32APSK
- Compatible with DVB-S、DVB-S2、CBS MPEG-4 and ABS-S Signal
- 3.5 Inch HD TFT LCD screen
- MPEG-2/MPEG-4/H.264 decoding Video format and 1080 Full HD



- Multi-purpose design
- Easy operation OSD design
- Quick satellite signal finding
- Program play、video monitoring
- Quick satellite antenna installation
- Global satellite data preset
- Satellite parameters editable
- Support DISEqC1.0、DISEqC1.1
- Easy operation DISEqC1.2、
- USALS OSD design
- Multiple satellites/TPs scan、blind scan and NIT scan
- Display POWER、BER、FEC、C/N NIT value

Specification:

- Sound prompt when signal locked
- Signal locked indicating light
- 13/18 volts indicating lights
- 22KHz indicating light
- LCD backlight turns off automatically
- LNB short-circuit protection and warning
- Audio and video input/output
- HDMI output
- Upgrade software & parameters through RS232, USB2.0
- Support USB PVR, MP3, JPG photo playback
- Removable battery design
- High capacity LI-ION battery (2550mA), can last around 3 hours
- Length x width x height : 17.5 x 12.5 x 3.5 cm
- Weight : 0.55Kg
- Gross weight : 1.25Kg
- Carton size : 56.5*37.5*24cm (10 pieces for one carton)
- Weight: 12Kg

Detailed Photos:

