

RTT

Round Taper Tool

- Unique spring loaded split jaw design allows **FAST & EASY** insertion, compression and removal of cable assembly
- Tool designed to be used with the following 360° Conical "Swedge" Connectors:
 - Arris/Telewire Digicon® Type II Series 6 & 59
 - F-Conn RG6 only radial type compression connector
- Toggle action allows minimal hand force and maximum strength to complete connector assembly
- Rugged, steel "O" Frame design with heat treated components, assures long operating life
- Unique adjustment features provide cable connector assembly reliability
- Full Cycle ratchet mechanism, with easy access escape lever, assures a complete assembly each and every time
- Improved HIGH VISIBILITY yellow cushion grips provide more comfort and like our original design will not rotate or slip during use
- Made in the U.S.A., U.S. Patent No.: 5,392,508; 5,596,800; 5,743,131; & 6,112,404
- Length: 11.50 in (292 mm) • Weight: 2.06 lbs (917 g)
- Part No.: 36315



TW Torque Wrenches

All our quality torque wrenches share many of the same features including...

- Prevent damage to equipment from over or under tightening
- Proper connectorization at "F" connector interface with factory preset torque setting
- Audible "clicking" sound to indicate proper calibrated torque
- High visibility yellow cushion grip body
- Model number, torque inch-pounds and wrench size stamped on tool for easy identification
- Available in multiple torque (inch-pound) settings and wrench sizes (see models below)
- Wrenches work in tightening mode only
- Made in the U.S.A.
- Length: 6.50 in (165 mm) • Weight: 6.5 oz (182 g)

TW

- Available in a range of **straight head** sizes
- **Tap port re-threader** on end of tool body
- Versions also available with insertion tool fitting on end of tool instead of tap port re-threader
- Handy, removable belt loop



Torque		Wrench Sizes & TW Model Numbers			
in Inch Pounds	in Newton Meters	*7/16 inch (11.1 mm)	1/2 inch (12.7 mm)	9/16 inch (14.3 mm)	5/8 inch (15.9 mm)
20	2.26	TW 207 (#35278)	TW 208 (#36275)	-	-
25	2.82	TW 257 (#38838)	-	-	-
30	3.39	TW 307 (#35260)	TW 308 (#35263)	TW 309 (#35280)	TW 3010 (#35283)
40	4.51	TW 407 (#35261)	TW 408 (#35264)	TW 409 (#35281)	TW 4010 (#35284)

* 7/16 in for universal "F" connectors