

HD-C20CV

INTEK
DIGITAL

HD Cable Verimatrix Zapper



Features

- High speed CPU performance (450MHz)
- MPEG-2 (MP@ML), MPEG-2 (MP@HL)
- MPEG-4 AVC/H.264 HP@L4
- Installation by easy setup guide
- Accurate friendly OSD with full function
- Multi-language menu
- DC II/DVB Subtitle, closed caption supported
- Easy to make favorite channel and parental lock function
- Last channel memory
- OTA update for software
- HDMI output
- RCA (L/R, Video) out

Partners



Technical Specifications

Tuner & Band Switching	
Front-End Input Frequency Connector	Single Cable 47~866GMHz IEC 600169-24 Female(RF IN) ,Loop out
Demodulator	
Demodulation Channel Bandwidth Symbol Rate FEC Mode	16,32, 64, 128, 256QAM 6,7,8 MHz 1.0 Msps ~ 7.0 Msps 1/2, 2/3, 3/4, 5/6, 7/8
Video Decoding	
Transport Stream Profile Level Video Format 2D Graphic Video System Video Resolution	MPEG-2 ISO/IEC 1318-1 MPEG-2 MP@ML, MPEG-2 MP@HL, MPEG-4 AVC/H.264 HP@L4,VC-1,DivX,XVID 4:3, 16:9,Pan & Scan,letter box 324Mpixels/sec,Advanced 2D/3D effect graphic engine PAL, NTSC 1080p,1080i, 720p, 480p,480i
Audio Decoding	
Audio Decoding Audio Mode Sampling Rate	MPEG-1, Musicam Layers 1&2,MP3,MPEG2- LayerII,DD,DD+,MPEG4 AAC,HE-AAC Single Channel, Dual Channel, Joint Stereo, Stereo 32, 44.1 & 48KHz
Chip & Memory	
CPU Flash Memory System Memory EEPROM	ST40 CPU core : 450MHz(STi7105) 8MByte DDR2 1Gbits x 2(256MByte) 8Kbyte
Conditional Access Interface	
CAS Smart Card Reader	Verimatrix standard(old Comvenient) SIM / Smart card Type embedded,ISO7816
A/V & Data In/Out	
Analog A/V HDMI USB Port	CVBS, Audio L/R Digital Video and Audio output(HDMI / HDCP Certified by 1.4a) USB 2.0 Host
Power Supply	
Input Voltage Power Consumption	AC100-250V~, 50/60Hz, External Adaptor(12V/2A) Max.24W (Standby : Less than 1W)
Physical Specification	
Net Weight Dimensions(W*H*D) Operating Temperature Storage Temperature	400g 180x37x132 0~50°C -10~+60°C

※ Note : The specifications are subject to change without prior notice.